

C2S



Technical Characteristics	Value	Units
Power for solenoid valves	14	W
DC supply for electro valves	24	Volts
Nominal current	0.6	A

Network

Max. network water flow	100	l/m
Max water network pressure	5	bar
Min water network pressure	3	bar
Water capacity	1	l
Water output temp	Network temp	-
Hydraulic connections circuit 1	1" M BSP	-
Hydraulic connections circuit 2	3/4" M BSP	-

Enclosure

Length, Width, Height	400 x 200 x 150	mm
Weight	15	kg

An ultra-compact mold cooling unit designed for heat and cool processes.

Ultra-compact Selection between two water circuits through a simple plug and play unit.

Easy to use Entirely remote controlled and powered by RocTool RT series.

Roctool S.A. reserves the right to change technical specifications without notice.

Roctool SA
Savoie Technolac
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
FRANCE
+33 479 26 27 07

Roctool Inc.
5900 Harris Technology Blvd.
Suite R
Charlotte, NC 98269-3784
USA
+1 980 938 0586

Roctool K.K.
Kudan Tamagawa Bldg. 4F
3-7-12, Kudan-Minami
Chiyoda-ku, Tokyo
JAPAN 102-0074
+81 3 6265 6889

Roctool Taiwan
6F, No. 83 Sec1
Chongqing S. Rd.
Zhongzheng Dist.
Taipei City, TAIWAN
+886 223 825 246

Roctool GmbH
Kreuzmattenstrasse 14
79423 Heitersheim
GERMANY
+49 7634 50829 285