

C6 micro-BF/W (vs)



Technical Characteristics	Value		Units
	C6	C6 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	8.5	8.7	A
AC Line power	5.9	6.6	kVA
Pump water flow (cooling)	100		l/m
Pump water flow (transfer)	67		l/m
Differential pressure available (cooling) (to be added to the network pressure)	4.4	(if pressure at 2.0 – Total 6.4)	bar
Pump Pressure (transfer)	4.8		bar
Water tank capacity	30		l
Water output temp.	Network temp.		-
Hydraulic connections	1" F		-
Compressed air connection	1" F		-
Compressed air max pressure	7		bar
Enclosure			
Length, Width, Height	897 x 442 x 752		mm
Weight empty	115		kg
Color	RAL 7035 & black		
Option			
	Bolting to floor	Wheels	
C6-BF	YES	NO	
C6-W	NO	YES	

An ultra-compact mold cooling unit designed for heat and cool processes.

- Efficient** Customized for heat and cool processes through mold cooling and purging solution.
- Easy to use** Entirely remote controlled and powered by RocTool RT series.
- Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

Roctool S.A. reserves the right to change technical specifications without notice.

Roctool SA
Savoie Technolac
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
FRANCE
+33 479 26 27 07

Roctool Inc.
5900 Harris Technology Blvd.
Suite R
Charlotte, NC 98269-3784
USA
+1 980 938 0586

Roctool K.K.
Kudan Tamagawa Bldg. 4F
3-7-12, Kudan-Minami
Chiyoda-ku, Tokyo
JAPAN 102-0074
+81 3 6265 6889

Roctool Taiwan
6F, No. 83 Sec1
Chongqing S. Rd.
Zhongzheng Dist.
Taipei City, TAIWAN
+886 223 825 246

Roctool GmbH
Kreuzmattenstrasse 14
79423 Heitersheim
GERMANY
+49 7634 50829 285