

## R75 micro-BF/W (vs)



Technical Characteristics	Value		Units
	R75	R75 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	8.45	8.45	A
AC Line power	5.9	5.9	kVA
Cooling capacity of exchanger	75		kW
Inlet temperature (from factory)	20-25		C°
Outlet temperature (to process)	28-33		C°
Primary Hydraulic connections	1" F BSP		-
Secondary Hydraulic connections	3/4" F		-
Water tank capacity	30		l
Secondary water flow	2 x 58		l/min
Primary fluid flow (pump excluded)	116		l/min
Pressure available	4.6		bar
<b>Enclosure</b>			
Length, Width, Height	905 x 442 x 752		mm
Weight empty	125		kg
Color	RAL 7035 & black		
<b>Option</b>			
	<b>Bolting to floor</b>	<b>Wheels</b>	
R75-BF	YES	NO	
R75-W	NO	YES	

An ultra-compact cooling unit designed for RocTool induction generators.

- Efficient** Ultra Compact hydraulic module adapted for cooling ROC series through two closed water loop.
- Easy to use** Entirely remote controlled by RocTool RT series (HMI).
- Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

RocTool S.A. reserves the right to change technical specifications without notice.

**RocTool SA**  
Savoie Technolac  
34 Allée du lac d'Aiguebelette  
73370 Le Bourget du Lac  
FRANCE  
+33 479 26 27 07

**RocTool Inc.**  
5900 Harris Technology Blvd.  
Suite R  
Charlotte, NC 98269-3784  
USA  
+1 980 938 0586

**RocTool K.K.**  
Kudan Tamagawa Bldg. 4F  
3-7-12, Kudan-Minami  
Chiyoda-ku, Tokyo  
JAPAN 102-0074  
+81 3 6265 6889

**RocTool Taiwan**  
6F, No. 83 Sec1  
Chongqing S. Rd.  
Zhongzheng Dist.  
Taipei City, TAIWAN  
+886 223 825 246

**RocTool GmbH**  
Kreuzmattenstrasse 14  
79423 Heitersheim  
GERMANY  
+49 7634 50829 285