

ROC-A 50



Technical Characteristics	Value	Units
Power	50	KW
AC Voltage (3 phases)	360-520	Volts
Frequency	50-60	Hz
AC Line Power	58	KVA max
Frequency Range	50-150	KHZ
Water Flow Generator	9.5	l/min
Water Flow Connection Box	3.8	l/min
Water Temp min/max	20-35	°C
Pressure min/max	2.8-5.51	bar
Cooling Water Quality	7	ph

Generator enclosure

Length, Width, Height	721 x 436 x 762	mm
Weight	68	kg

Connection Box enclosure

Length, Width, Height	457 x 203 x 229	mm
Weight	20	Kg

An ultra-compact induction generator dedicated for RocTool processing.

- Compact** ROC-A's design saves valuable floor space and simplifies in-line integration.
- User friendly** A remote control unit lets you control heating cycles via feedback to the microcontroller.
- Secured** ROC-A 50 steel cabinet and shielded electrics cables prevent from electromagnetical disturbance for nearest equipment.

Roctool S.A. reserves the right to change technical specifications without notice.

Roctool SA
Savoie Technolac
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
FRANCE
+33 479 26 27 07

Roctool Inc.
5900 Harris Technology Blvd.
Suite R
Charlotte, NC 98269-3784
USA
+1 980 938 0586

Roctool K.K.
Kudan Tamagawa Bldg. 4F
3-7-12, Kudan-Minami
Chiyoda-ku, Tokyo
JAPAN 102-0074
+81 3 6265 6889

Roctool Taiwan
6F, No. 83 Sec1
Chongqing S. Rd.
Zhongzheng Dist.
Taipei City, TAIWAN
+886 223 825 246

Roctool GmbH
Kreuzmattenstrasse 14
79423 Heitersheim
GERMANY
+49 7634 50829 285