

ROC-E 100 DZ



Technical Characteristics	Value	Units
Power	2 x 100	KW
AC Voltage (3 phases)	400-480	Volts
Frequency	50-60	Hz
AC Line Power	267	KVA max
Frequency Range	20-60	KHZ
Water Flow	36	l/min
Water Temp min/max	20-35	°C
Pressure min/max	4-6	bar
Cooling Water Quality	7-9	pH
Hydraulic connections	3/4" M	Inch
Color	RAL 7035 Grey	
Generator enclosure		
Length, Width, Height	600 x 500 x 1300	mm
Weight	250	kg
Connection Box enclosure		
Length, Width, Height	270 x 100 x 110	mm
Weight	5	Kg

An ultra-compact induction generator dedicated for RocTool processing.

- Double Zone** The double zone version features two independent power output that can operate simultaneously under identical or different parameter.
- User friendly** A remote control unit lets you control heating cycles via feedback to the microcontroller.
- Secured** ROC-E 100DZ steel cabinet and shielded electric cables prevent from electromagnetic disturbance for nearest equipment.

Roctool S.A. reserves the right to change technical specifications without notice.


Roctool SA
 Savoie Technolac
 34 Allée du lac d'Aiguebelette
 73370 Le Bourget du Lac
 FRANCE
 +33 479 26 27 07


Roctool Inc.
 5900 Harris Technology Blvd.
 Suite R
 Charlotte, NC 98269-3784
 USA
 +1 980 938 0586


Roctool K.K.
 Kudan Tamagawa Bldg. 4F
 3-7-12, Kudan-Minami
 Chiyoda-ku, Tokyo
 JAPAN 102-0074
 +81 3 6265 6889


Roctool Taiwan
 6F, No. 83 Sec1
 Chongqing S. Rd.
 Zhongzheng Dist.
 Taipei City, TAIWAN
 +886 223 825 246


Roctool GmbH
 Kreuzmattenstrasse 14
 79423 Heitersheim
 GERMANY
 +49 7634 50829 285