

ROC-E 100



Technical Characteristics	Value	Units
Power	100	KW
AC Voltage (3 phases)	400-480	Volts
Frequency	50-60	Hz
AC Line Power	134	KVA max
Frequency Range	20-60	KHZ
Water Flow	24	l/min
Water Temp min/max	20-35	°C
Pressure min/max	4-6	bar
Cooling Water Quality	7-9	pH
Hydraulic connections	3/4" M	Inch
Color	RAL 7035 Grey	
Generator enclosure		
Length, Width, Height	600 x 500 x 1300	mm
Weight	250	kg
Connection Box enclosure		
Length, Width, Height	270 x 100 x 110	mm
Weight	5	Kg

An ultra-compact induction generator dedicated for RocTool processing.

- / **Ultra-compact** ROC-E's design saves valuable floor space and simplifies in-line integration.
- / **User friendly** A remote control unit lets you control heating cycles via feedback to the microcontroller.
- / **Secured** ROC-E 100 steel cabinet and shielded electric cables prevent from electromagnetic disturbance for nearest equipment.

Roctool S.A. reserves the right to change technical specifications without notice.

Roctool SA
Savoie Technolac
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
FRANCE
+33 479 26 27 07

Roctool Inc.
5900 Harris Technology Blvd.
Suite R
Charlotte, NC 98269-3784
USA
+1 980 938 0586

Roctool K.K.
Kudan Tamagawa Bldg. 4F
3-7-12, Kudan-Minami
Chiyoda-ku, Tokyo
JAPAN 102-0074
+81 3 6265 6889

Roctool Taiwan
6F, No. 83 Sec1
Chongqing S. Rd.
Zhongzheng Dist.
Taipei City, TAIWAN
+886 223 825 246

Roctool GmbH
Kreuzmattenstrasse 14
79423 Heitersheim
GERMANY
+49 7634 50829 285