

T9 micro-BF/W (vs)



Technical Characteristics	Value		Units
	T9	T9 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	17.4	16.3	A
Power input	11.4	12.0	kW
AC Line power	11.4	6.6	kVA
Power of the therm. Reg. (heat / cool)	9/140*		kW
Pump water flow	100		l/m
Pump Pressure	4.4		bar
Water tank capacity	30		l
Water output temp.	20 to 90		°C
Hydraulic connections	1" F		-
Enclosure			
Length, Width, Height	900 x 300 x 760		mm
Weight empty	75		kg
Color	RAL 7035 & black		
Option			
	Bolting to floor	Wheels	
T9-BF	YES	NO	
T9-W	NO	YES	

An ultra-compact thermoregulator designed for heat and cool processes.

Efficient This temperature controller is particularly intended for applications requiring high flow rate and fast cooling. It has been designed to maintain the water process at a constant temperature from 20°C to 90°C (closed loop).

Ultra-compact Saves valuable floor space and simplified inline integration.

Roctool S.A. reserves the right to change technical specifications without notice.

Roctool SA
Savoie Technolac
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
FRANCE
+33 479 26 27 07

Roctool Inc.
5900 Harris Technology Blvd.
Suite R
Charlotte, NC 98269-3784
USA
+1 980 938 0586

Roctool K.K.
Kudan Tamagawa Bldg. 4F
3-7-12, Kudan-Minami
Chiyoda-ku, Tokyo
JAPAN 102-0074
+81 3 6265 6889

Roctool Taiwan
6F, No. 83 Sec1
Chongqing S. Rd.
Zhongzheng Dist.
Taipei City, TAIWAN
+886 223 825 246

Roctool GmbH
Kreuzmattenstrasse 14
79423 Heitersheim
GERMANY
+49 7634 50829 285