

## R60 micro-BF/W (vs)



Technical Characteristics	Value		Units
	R60	R60 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	8.45	8.45	A
AC Line power	5.9	5.9	kVA
Cooling capacity of exchanger		60	kW
Inlet temperature (from factory)		20-25	C°
Outlet temperature (to process)		28-33	C°
Primary Hydraulic connections		1" F BSP	-
Secondary Hydraulic connections		3/4" F	-
Water tank capacity		30	l
Secondary water flow		2 x 50	l/min
Primary fluid flow (pump excluded)		100	l/min
Pressure available		4.7	bar
<b>Enclosure</b>			
Length, Width, Height		905 x 442 x 752	mm
Weight empty		125	kg
Color		RAL 7035 & black	
<b>Option</b>			
	<b>Bolting to floor</b>		<b>Wheels</b>
R60-BF	YES		NO
R60-W	NO		YES

An ultra-compact cooling unit designed for Roctool induction generators.

- \ **Efficient** Ultra Compact hydraulic module adapted for cooling ROC series through two closed water loops.
- \ **Easy to use** Entirely remote controlled by Roctool RT series (HMI).
- \ **Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

*Roctool S.A. reserves the right to change technical specifications without notice.*

\  
 Roctool SA  
 Savoie Technolac – Modul R  
 34 Allée du lac d'Aiguebelette  
 73370 Le Bourget du Lac  
 France  
 +33 479 26 27 07