

## C12 micro-BF/W (vs)



Technical Characteristics	Value		Units
	C12	C12 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	10.7	8.7	A
AC Line power	7.4	6.6	kVA
Pump water flow (cooling)	200		l/m
Pump water flow (transfer)	170		l/m
Differential pressure available (cooling) (to be added to the network pressure)	4.0 (if pressure at 2.0 – Total 6.4)		bar
Pump Pressure (transfer)	4.4		bar
Water tank capacity	30		l
Water output temp.	Network temp.		-
Hydraulic connections	1" F		-
Compressed air connection	1" F		-
Compressed air max pressure	7		bar
<b>Enclosure</b>			
Length, Width, Height	897 x 442 x 752		mm
Weight empty	130		kg
Color	RAL 7035 & black		
<b>Option</b>			
	<b>Bolting to floor</b>	<b>Wheels</b>	
C12-BF	YES	NO	
C12-W	NO	YES	

An ultra-compact mold cooling unit designed for heat and cool processes.

- Efficient** Customized for heat and cool processes through mold cooling and purging solution.
- Easy to use** Entirely remote controlled and powered by RocTool RT series.
- Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

Roctool S.A. reserves the right to change technical specifications without notice.

**Roctool SA**  
Savoie Technolac  
34 Allée du lac d'Aiguebelette  
73370 Le Bourget du Lac  
FRANCE  
+33 479 26 27 07

**Roctool Inc.**  
5900 Harris Technology Blvd.  
Suite R  
Charlotte, NC 98269-3784  
USA  
+1 980 938 0586

**Roctool K.K.**  
Kudan Tamagawa Bldg. 4F  
3-7-12, Kudan-Minami  
Chiyoda-ku, Tokyo  
JAPAN 102-0074  
+81 3 6265 6889

**Roctool Taiwan**  
6F, No. 83 Sec1  
Chongqing S. Rd.  
Zhongzheng Dist.  
Taipei City, TAIWAN  
+886 223 825 246

**Roctool GmbH**  
Kreuzmattenstrasse 14  
79423 Heitersheim  
GERMANY  
+49 7634 50829 285