

# ROC-E 25 200V Air-cooled

Suitable for 200V network



Technical Characteristics	Value	Units
Power	25	kW
AC Voltage (3 phases)	200V	V
Frequency	50-60	Hz
AC Line Power	36.5	KVA max
Frequency Range	35-70	kHz
Method of cooling	Air cooled	
Max inlet temp. air	40	°C
Ambiant operating air temp.	+5 to +40	°C
Air consumption	120	m <sup>3</sup> /h

## Generator enclosure

Length, Width, Height	560x190x310	mm
Weight	24	kg
Enclosure protection	IP43	

An ultra-compact induction generator dedicated for Roctool processing.

- Plug & play** Air-cooled technology, lightweight. No additional footprint.
- Latest technology** High efficiency, silicon carbide components.
- Quick connection** Enhanced fast tool change possible.

Roctool S.A. reserves the right to change technical specifications without notice.

**Roctool SA**  
Savoie Technolac  
34 Allée du lac d'Aiguebelette  
73370 Le Bourget du Lac  
FRANCE  
+33 479 26 27 07

**Roctool Inc.**  
5900 Harris Technology Blvd.  
Suite R  
Charlotte, NC 98269-3784  
USA  
+1 980 938 0586

**Roctool K.K.**  
Kudan Tamagawa Bldg. 4F  
3-7-12, Kudan-Minami  
Chiyoda-ku, Tokyo  
JAPAN 102-0074  
+81 3 6265 6889

**Roctool Taiwan**  
6F, No. 83 Sec1  
Chongqing S. Rd.  
Zhongzheng Dist.  
Taipei City, TAIWAN  
+886 223 825 246

**Roctool GmbH**  
Kreuzmattenstrasse 14  
79423 Heitersheim  
GERMANY  
+49 7634 50829 285