

ROC-E 25 Air-cooled



Technical Characteristics	Value	Units
Power	25	kW
AC Voltage (3 phases)	400-480	V
Frequency	50-60	Hz
AC Line Power	36.5	KVA max
Frequency Range	35-70	kHz
Method of cooling	Air cooled	
Max inlet temp. air	40	°C
Ambiant operating air temp.	+5 to +40	°C
Air consumption	120	m ³ /h
Generator enclosure		
Length, Width, Height	560x190x310	mm
Weight	24	kg
Enclosure protection	IP43	

An ultra-compact induction generator dedicated for Roctool processing.

- Plug & play** Air-cooled technology, lightweight. No additional footprint.
- Latest technology** High efficiency, silicon carbide components.
- Quick connection** Enhanced fast tool change possible.

Roctool S.A. reserves the right to change technical specifications without notice.

Roctool SA
Savoie Technolac
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
FRANCE
+33 479 26 27 07

Roctool Inc.
5900 Harris Technology Blvd.
Suite R
Charlotte, NC 98269-3784
USA
+1 980 938 0586

Roctool K.K.
Kudan Tamagawa Bldg. 4F
3-7-12, Kudan-Minami
Chiyoda-ku, Tokyo
JAPAN 102-0074
+81 3 6265 6889

Roctool Taiwan
6F, No. 83 Sec1
Chongqing S. Rd.
Zhongzheng Dist.
Taipei City, TAIWAN
+886 223 825 246

Roctool GmbH
Kreuzmattenstrasse 14
79423 Heitersheim
GERMANY
+49 7634 50829 285