

ROC-E 150 DZ



Technical Characteristics

	Value	Units
Power	2 x 150	KW
AC Voltage (3 phases)	400-480	Volts
Frequency	50-60	Hz
AC Line Power	389	KVA max
Frequency Range	20-60	KHZ
Water Flow	36	l/min
Water Temp min/max	20-35	°C
Pressure min/max	4-6	bar
Cooling Water Quality	7-9	pH
Hydraulic connections	3/4" M	Inch
Color	RAL 7035 Grey	

Generator enclosure

Length, Width, Height	600 x 500 x 1300	mm
Weight	250	kg

Connection Box enclosure

Length, Width, Height	270 x 100 x 110	mm
Weight	5	Kg

An ultra-compact induction generator dedicated for RocTool processing.

- \ **Double Zone** The double zone version features two independent power output that can operate simultaneously under identical or different parameter.
- \ **User friendly** A remote control unit lets you control heating cycles via feedback to the microcontroller.
- \ **Secured** ROC-E 150DZ steel cabinet and shielded electric cables prevent from electromagnetic disturbance for nearest equipment.

Roctool S.A. reserves the right to change technical specifications without notice.

\
Roctool SA
Savoie Technolac
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
FRANCE
+33 479 26 27 07

\
Roctool Inc.
5900 Harris Technology Blvd.
Suite R
Charlotte, NC 98269-3784
USA
+1 980 938 0586

\
Roctool K.K.
Kudan Tamagawa Bldg. 4F
3-7-12, Kudan-Minami
Chiyoda-ku, Tokyo
JAPAN 102-0074
+81 3 6265 6889

\
Roctool Taiwan
6F, No. 83 Sec1
Chongqing S. Rd.
Zhongzheng Dist.
Taipei City, TAIWAN
+886 223 825 246

\
Roctool GmbH
Kreuzmattenstrasse 14
79423 Heitersheim
GERMANY
+49 7634 50829 285