

## ROC-E 300



Technical Characteristics	Value	Units
Power	300	KW
AC Voltage (3 phases)	400-480	Volts
Frequency	50-60	Hz
AC Line Power	389	KVA max
Frequency Range	20-60	KHZ
Water Flow	36	l/min
Water Temp min/max	20-35	°C
Pressure min/max	4-6	bar
Cooling Water Quality	7-9	pH
Hydraulic connections	3/4" M	Inch
Color	RAL 7035 Grey	
<b>Generator enclosure</b>		
Length, Width, Height	600 x 500 x 1300	mm
Weight	250	kg
<b>Connection Box enclosure</b>		
Length, Width, Height	270 x 100 x 110	mm
Weight	5	Kg

An ultra-compact induction generator dedicated for RocTool processing.

- / **Ultra-compact** ROC-E's design saves valuable floor space and simplifies in-line integration.
- / **User friendly** A remote control unit lets you control heating cycles via feedback to the microcontroller.
- / **Secured** ROC-E 300 steel cabinet and shielded electric cables prevent from electromagnetic disturbance for nearest equipment.

Roctool S.A. reserves the right to change technical specifications without notice.

**Roctool SA**  
Savoie Technolac  
34 Allée du lac d'Aiguebelette  
73370 Le Bourget du Lac  
FRANCE  
**+33 479 26 27 07**

**Roctool Inc.**  
5900 Harris Technology Blvd.  
Suite R  
Charlotte, NC 98269-3784  
USA  
**+1 980 938 0586**

**Roctool K.K.**  
Kudan Tamagawa Bldg. 4F  
3-7-12, Kudan-Minami  
Chiyoda-ku, Tokyo  
JAPAN 102-0074  
**+81 3 6265 6889**

**Roctool Taiwan**  
6F, No. 83 Sec1  
Chongqing S. Rd.  
Zhongzheng Dist.  
Taipei City, TAIWAN  
**+886 223 825 246**

**Roctool GmbH**  
Kreuzmattenstrasse 14  
79423 Heitersheim  
GERMANY  
**+49 7634 50829 285**