

C24 micro-BF/W (vs)



| Technical Characteristics | Value | | Units |
|--|--|---------------|-------|
| | C24 | C24 vs | |
| Voltage (3 phases) | 400 | 440 | V |
| Frequency | 50 | 60 | Hz |
| Nominal current | 17 | 13 | A |
| AC Line power | 11.8 | 6.6 | kVA |
| Pump water flow (cooling) | 2 x 200 | | l/m |
| Pump water flow (transfer) | 170 | | l/m |
| Differential pressure available (cooling) (to be added to the network pressure) | 4.0 <small>(if pressure at 2.0 – Total 6.4)</small> | | bar |
| Pump Pressure (transfer) | 4.4 | | bar |
| Water tank capacity | 84 | | l |
| Water output temp. | Network temp. | | - |
| Hydraulic connections | 2" F | | - |
| Compressed air connection | 1" F | | - |
| Compressed air max pressure | 7 | | bar |
| Enclosure | | | |
| Length, Width, Height | 897 x 592 x 1392 | | mm |
| Weight empty | 190 | | kg |
| Color | RAL 7035 & black | | |
| Option | | | |
| | Bolting to floor | Wheels | |
| C24-BF | YES | NO | |
| C24-W | NO | YES | |

A mold cooling unit designed for heat and cool processes.

- Efficient** Customized for heat and cool processes trough mold cooling and purging solution.
- Easy to use** Entirely remote controlled and powered by Roctool RT series.
- Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

Roctool S.A. reserves the right to change technical specifications without notice.

Roctool SA
Savoie Technolac – Modul R
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
France
+33 479 26 27 07