

R60 micro-BF/W (vs)



Technical Characteristics	Value		Units
	R60	R60 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	8.45	8.45	A
AC Line power	5.9	5.9	kVA
Cooling capacity of exchanger	60		kW
Inlet temperature (from factory)	20-25		C°
Outlet temperature (to process)	28-33		C°
Primary Hydraulic connections	1" F BSP		-
Secondary Hydraulic connections	3/4" F		-
Water tank capacity	30		l
Secondary water flow	2 x 50		l/min
Primary fluid flow (pump excluded)	100		l/min
Pressure available	4.7		bar
Enclosure			
Length, Width, Height	905 x 442 x 752		mm
Weight empty	125		kg
Color	RAL 7035 & black		
Option			
	Bolting to floor		Wheels
R60-BF	YES		NO
R60-W	NO		YES

An ultra-compact cooling unit designed for Roctool induction generators.

- \ **Efficient** Ultra Compact hydraulic module adapted for cooling ROC series through two closed water loops.
- \ **Easy to use** Entirely remote controlled by Roctool RT series (HMI).
- \ **Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

Roctool S.A. reserves the right to change technical specifications without notice.

\
 Roctool SA
 Savoie Technolac – Modul R
 34 Allée du lac d'Aiguebelette
 73370 Le Bourget du Lac
 France
 +33 479 26 27 07