

## T9 micro-BF/W (vs)



Technical Characteristics	Value		Units
	T9	T9 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	17.4	16.3	A
Power input	11.4	12.0	kW
AC Line power	11.4	6.6	kVA
Power of the therm. Reg. (heat / cool)	9/140*		kW
Pump water flow	100		l/m
Pump Pressure	4.4		bar
Water tank capacity	30		l
Water output temp.	20 to 90		°C
Hydraulic connections	1" F		-
<b>Enclosure</b>			
Length, Width, Height	900 x 300 x 760		mm
Weight empty	75		kg
Color	RAL 7035 & black		
<b>Option</b>			
	<b>Bolting to floor</b>	<b>Wheels</b>	
T9-BF	YES	NO	
T9-W	NO	YES	

An ultra-compact thermoregulator designed for heat and cool processes.

**Efficient** This temperature controller is particularly intended for applications requiring high flow rate and fast cooling. It has been designed to maintain the water process at a constant temperature from 20°C to 90°C (closed loop).

**Ultra-compact** Saves valuable floor space and simplified inline integration.

*Roctool S.A. reserves the right to change technical specifications without notice.*

**Roctool SA**  
Savoie Technolac – Modul R  
34 Allée du lac d'Aiguebelette  
73370 Le Bourget du Lac  
France  
**+33 479 26 27 07**