

C24 micro-BF/W (vs)



Technical Characteristics	Value		Units
	C24	C24 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	17	13	A
AC Line power	11.8	6.6	kVA
Pump water flow (cooling)	2 x 200		l/m
Pump water flow (transfer)	170		l/m
Differential pressure available (cooling) <small>(to be added to the network pressure)</small>	4.0 <small>(if pressure at 2.0 – Total 6.4)</small>		bar
Pump Pressure (transfer)	4.4		bar
Water tank capacity	84		l
Water output temp.	Network temp.		-
Hydraulic connections	2" F		-
Compressed air connection	1" F		-
Compressed air max pressure	7		bar
Enclosure			
Length, Width, Height	897 x 592 x 1392		mm
Weight empty	190		kg
Color	RAL 7035 & black		
Option			
	Bolting to floor	Wheels	
C24-BF	YES	NO	
C24-W	NO	YES	

A mold cooling unit designed for heat and cool processes.

- Efficient** Customized for heat and cool processes trough mold cooling and purging solution.
- Easy to use** Entirely remote controlled and powered by Roctool RT series.
- Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

Roctool S.A. reserves the right to change technical specifications without notice.

R
Roctool SA
Savoie Technolac – Modul R
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
France
+33 479 26 27 07