

R45 micro-BF/W (vs)



Technical Characteristics	Value		Units
	R45	R45 vs	
Voltage (3 phases)	400	440	V
Frequency	50	60	Hz
Nominal current	4.5	4.5	A
AC Line power	3.1	3.5	kVA
Cooling capacity of exchanger		45	kW
Inlet temperature (from factory)		20-25	C°
Outlet temperature (to process)		28-33	C°
Primary Hydraulic connections		1" F BSP	-
Secondary Hydraulic connections		3/4" F	-
Water tank capacity		30	l
Secondary water flow		66	l/min
Primary fluid flow (pump excluded)		66	l/min
Pressure available		4.7	bar
Enclosure			
Length, Width, Height		900 x 300 x 760	mm
Weight empty		70	kg
Color		RAL 7035 & black	
Option			
	Bolting to floor		Wheels
R45-BF	YES		NO
R45-W	NO		YES

An ultra-compact cooling unit designed for Roctool induction generators.

- Efficient** Ultra Compact hydraulic module adapted for cooling ROC series through two closed water loop.
- Easy to use** Entirely remote controlled by Roctool RT series (HMI).
- Secured** Implement general switch, high water level security, real time indicators and signaling lamp.

Roctool S.A. reserves the right to change technical specifications without notice.

R
Roctool SA
Savoie Technolac – Modul R
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
France
+33 479 26 27 07