

## ROC-G 150 DZ



| Technical Characteristics       | Value            | Units   |
|---------------------------------|------------------|---------|
| Power                           | 2 x 150          | KW      |
| AC Voltage (3 phases)           | 400-480          | Volts   |
| Frequency                       | 50-60            | Hz      |
| AC Line Power                   | 375              | KVA max |
| Frequency Range                 | 20-60            | KHZ     |
| Water Flow                      | 48               | l/min   |
| Water Temp min/max              | 20-38            | °C      |
| Pressure min/max                | 4-6              | bar     |
| Cooling Water Quality           | 7-9              | pH      |
| Hydraulic connections           | 1" M             | Inch    |
| Color                           | RAL 7035 Grey    |         |
| <b>Generator enclosure</b>      |                  |         |
| Length, Width, Height           | 600 x 500 x 1600 | mm      |
| Weight                          | 355              | kg      |
| <b>Connection Box enclosure</b> |                  |         |
| Length, Width, Height           | (x2) 320x130x140 | mm      |
| Weight                          | (x2) 5           | Kg      |

An induction generator dedicated for Roctool processing.

- \ **Double Zone** The double zone version features two independent power outputs that can operate simultaneously under identical or different parameters.
- \ **User friendly** A remote control unit lets you control heating cycles via feedback to the microcontroller.
- \ **Secured** ROC-G 150DZ steel cabinet and shielded electrical cables prevent from electromagnetic disturbance for nearest equipment.

*Roctool S.A. reserves the right to change technical specifications without notice.*

\  
 Roctool SA  
 Savoie Technolac – Modul R  
 34 Allée du lac d'Aiguebelette  
 73370 Le Bourget du Lac  
 France  
 +33 479 26 27 07