

ROC-A 50



Technical Characteristics	Value	Units
Power	50	KW
AC Voltage (3 phases)	360-520	Volts
Frequency	50-60	Hz
AC Line Power	58	KVA max
Frequency Range	50-150	KHZ
Water Flow Generator	9.5	l/min
Water Flow Connection Box	3.8	l/min
Water Temp min/max	20-35	°C
Pressure min/max	2.8-5.51	bar
Cooling Water Quality	7	ph

Generator enclosure

Length, Width, Height	721 x 436 x 762	mm
Weight	68	kg

Connection Box enclosure

Length, Width, Height	457 x 203 x 229	mm
Weight	20	Kg

A compact induction generator dedicated for Roctool processing.

- \ **Compact** ROC-A's design saves valuable floor space and simplifies in-line integration.
- \ **User friendly** A remote control unit lets you control heating cycles via feedback to the microcontroller.
- \ **Secured** ROC-A 50 steel cabinet and shielded electrical cables prevent from electromagnetic disturbance for nearest equipment.

Roctool S.A. reserves the right to change technical specifications without notice.

\
 Roctool SA
 Savoie Technolac – Modul R
 34 Allée du lac d'Aiguebelette
 73370 Le Bourget du Lac
 France
 +33 479 26 27 07