

T9 micro-BF/W (vs)



| Technical Characteristics | Value | | Units |
|--|-------------------------|-------|---------------|
| | T9 | T9 vs | |
| Voltage (3 phases) | 400 | 440 | V |
| Frequency | 50 | 60 | Hz |
| Nominal current | 17.4 | 16.3 | A |
| Power input | 11.4 | 12.0 | kW |
| AC Line power | 11.4 | 6.6 | kVA |
| Power of the therm. Reg. (heat / cool) | 9/140* | | kW |
| Pump water flow | 100 | | l/m |
| Pump Pressure | 4.4 | | bar |
| Water tank capacity | 30 | | l |
| Water output temp. | 20 to 90 | | °C |
| Hydraulic connections | 1" F | | - |
| Enclosure | | | |
| Length, Width, Height | 900 x 300 x 760 | | mm |
| Weight empty | 75 | | kg |
| Color | RAL 7035 & black | | |
| Option | | | |
| | Bolting to floor | | Wheels |
| T9-BF | YES | | NO |
| T9-W | NO | | YES |

An ultra-compact thermoregulator designed for heat and cool processes.

Efficient This temperature controller is particularly intended for applications requiring high flow rate and fast cooling. It has been designed to maintain the water process at a constant temperature from 20°C to 90°C (closed loop).

Ultra-compact Saves valuable floor space and simplified inline integration.

Roctool S.A. reserves the right to change technical specifications without notice.

Roctool SA
Savoie Technolac – Modul R
34 Allée du lac d'Aiguebelette
73370 Le Bourget du Lac
France
+33 479 26 27 07